

SeaTrace 3000®



3.78 inch (96 mm)

1,300	SeaTrace 3000°	SeaTrace 3000° Advanced	SeaTrace 3000°Pro
Power supply	3 x IFR18500 3.2 V 1 AH	3 x IFR18500 3.2 V 1 AH	3 x IFR18500 3.2 V 1 AH
Luminous intensity	Maximum 5.6 cd	Maximum 5.6 cd	Maximum 5.6 cd
Intensity	Continous intensity over the whole operating time! No decrease!	Continous intensity over the whole operating time! No decrease!	Continous intensity over the whole operating time! No decrease!
Max. operation depth	2640 ft. / 800 m	3300 ft. / 1000 m	3300 ft. / 1000 m
Max. diameter	3.78 inch / 96 mm	3.78 inch / 96 mm	3.78 inch / 96 mm
Runtime at O degrees °C	200 h full + 150 h flickering	depending of configuration	depending of configuration
Recharge time	6.5 h	6.5 h	6.5 h
Colors		Colour change with Bluetooth connection and mobile APP for android / IOS	Colour change with Bluetooth connection and mobile APP for android / IOS
Noise generator			Acoustic Attraction

CRAB/LOBSTER LIGHT CONTROL

CRAB/LOBSTER LIGHT CONTROL